


MAIN FEATURES

- Compact Design
- European Material
- Load Limiter
- Hoisting Limit Switch
- Travelling Limit Switch
- Chain Collector
- Single or Double Poles Motors
- Electro-Magnetic Disk Brakes
- Swivelling Hook with safety latch
- Atex Version Zone 1 or 2 IIA/B/C
- Atex version Zone 21/22
- IECEx Version
- EAC Version also TR-CU-012
- AS Australian Standards
- UL/NEMA version



SPECIFICATIONS / DIMENSIONS (mm)

Chain size Diameter in mm	FEM duty	ISO duty	Capacity in kg	Lifting speed rpm		No. of falls	Motor kw main/creep	Motor RPM	'A' Headroom			B	C	G	H	L	Wt.(kg) Hook susp. 3m lift	Wt.(kg) with ET 3m lift																								
				Single	Dual				HOOK SUSP.	PT	GT/ET																															
4	1Am	M4	125	8	ONE	0.25	1500	360	400	420	238	128	31.5	250	230	30	65																									
				8/2.6	ONE	0.25/0.08	1500/410	360	400	420																																
			4	ONE	0.25	1500	360	400	420																																	
			4/1.3	ONE	0.25/0.08	1500/410	360	400	420																																	
6	1Am	M4	250	8	ONE	0.55	1500	440	460	480			238	128	31.5	350	280	40	75																							
				8/2.6	ONE	0.55/0.18	1500/410	440	460	480																																
			4	ONE	0.55	1500	440	460	480																																	
			4/1.3	ONE	0.55/0.18	1500/410	440	460	480																																	
7	1Am	M4	500	8	ONE	0.9	1500	440	460	480	238	128			31.5	390	290	55	90																							
				8/2.6	ONE	0.85/0.3	1500/460	550	560	580																																
			4	ONE	0.9	1500	550	560	580																																	
			4/1.3	ONE	0.85/0.3	1500/460	550	560	580																																	
10	1Am	M4	1000	8	ONE	1.84	1500	600	625	625			350	157	31.5	445	380	90	125																							
				8/2.6	ONE	1.7/0.6	1500/460	600	625	625																																
				4	ONE	1.84	1500	600	625	625																																
				4/1.3	ONE	1.7/0.6	1500/460	600	625	625																																
			2000	4	ONE	2.2	1500	600	625	625	37.5	445			380	90	135																									
																		3000	4	TWO	3.5	1500	950	870	870	45.5	300	400	125	185												
																															4	TWO	3.5/1.2	1500/460	950	870	870	45.5	300	400	135	200
4	TWO	4.5/1.5	1500/460	1000	NA	1000	53	300	400	160	250																															

Data tolerance ± 10%

The way to lift your ideas and your things



E.T.S. engineering
trasporto sollevamento s.p.a.
Zona Ind.le Ganga, 153
61045 Pergola (PU) Italy

Tel. +39 0721.775450 - 775452
Fax +39 0721.775451
<http://www.ets-spa.com>
e-mail: ets@ets-spa.com

Agenzia delle entrate di Fano
Reg. Impr. PU 01304960410
R.E.A. 122327 Pesaro
C. F. e Part. IVA IT01304960410
Cap. Soc. € 375.000,00 i.v.